

Nanotechnology-based flexible electronics

This content has been downloaded from IOPscience. Please scroll down to see the full text.

2012 Nanotechnology 23 340201

(<http://iopscience.iop.org/0957-4484/23/34/340201>)

View the [table of contents for this issue](#), or go to the [journal homepage](#) for more

Download details:

IP Address: 147.46.56.173

This content was downloaded on 17/02/2014 at 10:04

Please note that [terms and conditions apply](#).

EDITORIAL

Nanotechnology-based flexible electronics

Vivek Subramanian*University of California,
Berkeley, CA, USA*
viveks@eecs.berkeley.edu**Takhee Lee***Seoul National University,
Seoul, Korea*
tlee@snu.ac.kr

Research on flexible electronics has grown exponentially over the last decade. Researchers around the globe are developing a wide range of flexible systems, including displays [1, 2], sensors [3–5], RFID tags [6, 7] and other similar devices [8]. Innovations in materials have been key to the increased research success in this field of research in recent years [9]. Transistors, interconnects, memory cells, passive components and other assorted devices all have challenging material demands for flexible electronics to become a reality. Nanomaterials of various kinds have been found to represent a tremendously powerful tool, with nanoparticles [10], nanotubes, nanowires [3, 11] and engineered organic molecules [12, 13] contributing to the realization of high-performance semiconductors, dielectrics and conductors for flexible electronics applications.

Nanomaterials offer tunability in terms of performance, solution processability and processing temperature requirements, which makes them very attractive as building blocks for flexible electronic systems. Indeed, such systems represent some of the largest families of commercially produced nanomaterials today, and numerous commercial products based on nanoparticle formulations are widely available.

This special issue focuses on the rapidly blossoming field of flexible electronics, with a particular focus on the use of nanotechnology to facilitate flexible electronic materials, processes, devices and systems. Contributions to the issue describe the development of nanomaterials—including nanoparticles, nanotubes, nanowires and carbon-based thin films—for use in conductors, transparent electrodes, semiconductors and dielectrics. The articles feature innovations in nanomanufacturing and novel materials, as well as the application of these technologies to advanced flexible devices and systems.

As flexible electronics systems move rapidly towards successful commercial deployment, it is extremely likely that they will exploit nanomaterials as building blocks. Developments in the field will help to leverage the power of these materials to realize novel functionalities in flexible form factors. This special issue provides a view of the state of the art in these technologies, and gives a vision of the coming innovations that will make flexible electronics a reality.

References

- [1] Gelinck G H *et al* 2004 Flexible active-matrix displays and shift registers based on solution-processed organic transistors *Nature Mater.* **3** 106–10
- [2] Zhou L, Wang A, Wu S C, Sun J, Park S and Jackson T N 2006 All-organic active matrix flexible display *Appl. Phys. Lett.* **88** 083502
- [3] Fan Z, Ho J C, Jacobson Z A, Razavi H and Javey A 2008 Large-scale, heterogeneous integration of nanowire arrays for image sensor circuitry *Proc. Natl Acad. Sci.* **105** 11066
- [4] Sekitani T *et al* 2009 Organic nonvolatile memory transistors for flexible sensor arrays *Science* **326** 1516–9
- [5] Mannsfeld S C B *et al* 2010 Highly sensitive flexible pressure sensors with microstructured rubber dielectric layers *Nature Mater.* **9** 859–64
- [6] Subramanian V, Frechet J M J, Chang P C, Huang D C, Lee J B, Molesa S E, Murphy A R, Redinger D R and Volkman S K 2005 Progress toward development of all-printed RFID tags: materials, processes, and devices *Proc. IEEE* **93** 1330–8
- [7] Jung M *et al* 2010 All-printed and roll-to-roll-printable 13.56 MHz-operated 1 bit RF tag on plastic foils *IEEE Trans. Electron. Devices* **57** 571–80
- [8] Kim D-H *et al* 2011 Epidermal electronics *Science* **333** 838–43
- [9] Wagner S and Bauer S 2012 Materials for stretchable electronics *MRS Bull.* **37** 207

- [10] Grouchko M, Kamyshny A and Magdassi S 2009 Formation of air-stable copper–silver core–shell nanoparticles for inkjet printing *J. Mater. Chem.* **19** 3057–62
- [11] Takei K *et al* 2010 Nanowire active-matrix circuitry for low-voltage macroscale artificial skin *Nature Mater.* **9** 821–6
- [12] Sekitani T, Zschieschang U, Klauk H and Someya T 2010 Flexible organic transistors and circuits with extreme bending stability *Nature Mater.* **9** 1015–22
- [13] Park S, Wang G, Cho B, Kim Y, Song S, Ji Y, Yoon M and Lee T 2012 Flexible molecular-scale electronic devices *Nature Nanotechnol.* **7** 438–42